



Click Here ---->

destroy!
BUSINESS SHREDDERS

➔ 3105 CENTRALIZED OFFICE SHREDDER WITH AUTOMATIC OILER

"SPS" (Safety Protection System) package: electronically controlled, transparent safety shield in the feed opening; "Easy Switch" control element uses color codes and back-lit symbols to indicate operational status; automatic reverse and power cut-off (avoids paper jams); automatic power cut-off when shred bag is full or when cabinet door is opened; double protection against overheating; "ESM" (Energy Saving Mode) after 1 hour of inactivity | automatic start and stop controlled by photo cell | "ECC" (Electronic Capacity Control) indicator helps prevent paper jams by indicating sheet capacity levels during the shredding process | automatic oil injection insures optimal performance at all times | wide, 12" feed opening | high quality, hardened steel cutting shafts take staples, paper clips, credit cards, and CDs (strip- and cross-cut models) | super micro-cut (SMC) model meets all NSA/CSS specifications and is DOD approved | lifetime warranty on the cutting shafts (strip- and cross-cut models) | 1 year warranty on SMC cutting shafts | quiet and powerful single phase motor rated for continuous operation | sturdy chain drive and dust-proof gear box housing | high quality wooden cabinet mounted on casters | pull-out bag frame mechanism mounted on rollers for easy replacement of disposable shred bags (SMC model equipped with 26 gallon shred bin) | 48 gallon shred volume (approximate)

Dimensions (D x W x H): 23 x 22 x 40 inches, Shipping weight: 324 lbs.



20 amp. dedicated line required



CAPACITY INDICATOR



"ECC" (Electronic Capacity Control) indicator monitors capacity levels during operation.

➔ 3105 STRIP-CUT

| | |
|-----------------|--------|
| Strip width | 1/4" |
| Sheet capacity | 50-52* |
| Security level | 2 |
| Feed opening | 12" |
| Max. horsepower | 2 1/2 |

➔ 3105 CROSS-CUT

| | |
|-----------------|----------------|
| Particle size | 3/16" x 1 1/2" |
| Sheet capacity | 30-32* |
| Security level | 3 |
| Feed opening | 12" |
| Max. horsepower | 2 1/2 |

➔ 3105 CROSS-CUT

| | |
|-----------------|--------------|
| Particle size | 3/32" x 5/8" |
| Sheet capacity | 18-20* |
| Security level | 4 |
| Feed opening | 12" |
| Max. horsepower | 2 1/2 |

➔ 3105 SMC HIGH SECURITY

| | |
|-----------------|---------------|
| Particle size | 1/32" x 3/16" |
| Sheet capacity | 12-16* |
| Security level | 6 |
| Feed opening | 12" |
| Max. horsepower | 2 1/2 |

* may vary due to variations in paper and power supply

All technical data is approximate and subject to change. © MBM Corporation, 3/2009.

Dealer:



3134 Industry Drive
North Charleston, South Carolina 29418
800-223-2508, fax: 843-552-2974
www.mbmcorp.com



1675 Sismet Road, unit 4
Mississauga, Ontario L4W 4K8
800-387-2528, fax: 905-840-1114
www.ideal-mbm.com